

Robotics

Exercise 2

Marc Toussaint

Lecturer: Duy Nguyen-Tuong

TAs: Philipp Kratzer, Janik Hager, Yoojin Oh

Machine Learning & Robotics lab, U Stuttgart

Universitätsstraße 38, 70569 Stuttgart, Germany

October 25, 2018

0 MLR robotics-course

We will start with coding exercises in the next exercise sheet. On github <https://github.com/MarcToussaint/robotics-course> you can already find our course repository and an instruction on how to install it. Make yourself familiar with the code and run the tutorial (docs/1-basics.ipynb). For coding exercises we will provide both, c++ and python templates. You will be able to choose which one to use.

1 Geometry (3 Points)

a) You have a book (coordinate frame B) lying on the table (world frame W). Initially B and W are identical. Now you move the book 1 unit to the right, then rotate it by 45° counter-clock-wise around its origin. Given a dot p marked on the book at position $p^B = (1, 1)$ in the book coordinate frame, what are the coordinates p^W of that dot with respect to the world frame?

b) Given a point x with coordinates $x^W = (0, 1)$ in world frame, what are its coordinates x^B in the book frame?

c) What is the *coordinate* transformation from world frame to book frame, and from book frame to world frame?

Please use homogeneous coordinates to derive these answers. (See <http://ipvs.informatik.uni-stuttgart.de/mlr/marc/notes/3d-geometry.pdf> for more details on 3D geometry.)

2 Task spaces and Jacobians (7 Points)

In the lecture we introduced the basic kinematic maps $\phi_{i,v}^{\text{pos}}(q)$ and $\phi_{i,v}^{\text{vec}}(q)$, and their Jacobians, $J_{i,v}^{\text{pos}}(q)$ and $J_{i,v}^{\text{vec}}(q)$, where i may refer to any part of the robot and v is any point or direction on this part. In the following you may assume that we have routines to compute these for any q . The problem is to express other kinematic maps and their Jacobians in terms of these knowns. In the following you're asked to define more involved kinematics maps (a.k.a. task maps) $\phi(q)$ to solve certain motion problems. Please formulate all these maps such that the overall optimization problem is

$$f(q) = \|q - q_0\|_W^2 + \|\phi(q)\|^2$$

that is, the motion aims to minimize $\phi(q)$ to zero (absorb the y^* in the definition of ϕ .)

a) You would like to control a standard endeffector position p_{eff} to be at y^* , as usual. Can you define a 1-dimensional task map $\phi: \mathbb{R}^n \rightarrow \mathbb{R}$ to achieve this? What is its Jacobian? (2P)

b) You would like the two hands or the robot to become parallel (e.g. for clapping). What task map can you define to achieve this? What is the Jacobian? (2P)

c) Assume you would like to control the pointing direction of the robot's head (e.g., its eyes) to point to a desired external world point x^W . What task map can you define to achieve this? What is the Jacobian? (3P)